

NEMOSHIP



Co-funded by
the European Union

GA No. 101096324

NEMOSHIP: DIGITAL PLATFORM FOR OPTIMAL BESS USE

February 6th 2026

Roberta Luca
Călin Husar

SIEMENS

OVERVIEW OF THE PLATFORM CAPABILITIES



cidetec >
energy storage

Corvus  Energy

elkon

equinor 

In Extenso
Innovation Croissance

 **PONANT**

SDI

SIEMENS

 **SOLSTAD OFFSHORE**

VUB VRIJE
UNIVERSITEIT
BRUSSEL



NEMOSHIP

CONTENTS

1. Nemoship project
2. Digital Models
3. Digital Platform functionalities



Co-funded by
the European Union



NEMOSHIP

NEMOSHIP PROJECT




| NEMOSHIP | | https://nemoship.eu/ |
|-----------------|---|---|
| Title | NEw MOdular electrical architecture & digital platform to optimise large battery systems on SHIPs | |
| Call ID | HORIZON-CL5-2022-D5-01-01 - Exploiting electrical energy storage systems and better optimising large battery electric power within fully battery electric and hybrid ships (ZEWT Partnership) | |
| Type | Innovation Action | |
| Lead | CEA | |
| Duration | 4 years - 01/01/2023 to 31/12/2026 | |
| Total cost | 11.3 M Euros | |
| EU contribution | 7.9 M Euros | |

PROJECT EXPECTED OUTCOMES




NEMOSHIP



2 main innovative solutions:

- A modular and standardised 1.1 MWh battery energy storage solution enabling to exploit different types of batteries (HE and HP)
- A cloud-based digital platform enabling a data-driven optimal and safe exploitation





Consortium:

- 6 countries
- 11 complementary partners

Covering the entire value chain:

- 3 Research Technology Organization (CEA, VUB, Cidetec)
- 1 SME (SDI)
- 7 private large groups (Siemens, Corvus, Elkon, Solstad, Equinor, Ponant, In Extenso)



OBJECTIVES OF THE PROJECT



NEMOSHIP

1. Flexible electrification solutions to exploit heterogeneous storage units for a wide range of needs

- Limit the number of system components
- Widen the grid services provided by large battery systems
- Decrease CAPEX thanks to hybridisation
- Improve battery lifetime

2. Standardisation of the battery systems integration process and interfaces within the vessels

- Decrease BESS installation costs around 40%
- Contribute in LTI (Lost Time Incident / Injuries) reduction
- Increase maintenance capability of the crew members

3. Advanced tools for ship operators and owners to reach an optimal and safe exploitation

- Interface with existing third-party software used
- improve global efficiency of ESS exploitation of above 10%
- Decrease maintenance occurrences
- Increase number of crew members trained

4. Extending zero emission ability for both hybrid and full-electric ships


- Increase zero-emission transit
- Decrease CII (Carbon Intensity Index) for each vessel
- Improve full-electric arrangement sailing distance

➤ **Outcome 1:** Development and validation of a 1.5 MWh modular BESS and its BPMS for a retrofitted hybrid vessel

➤ **Outcome 2:** Provide integration methodologies and standards thanks to a Formal Safety Assessment

➤ **Outcome 3:** Development and validation of a cloud-based digital platform enabling a data-driven exploitation

➤ **Outcome 4:** Two real hybrid demonstration vessels reaching above TRL7 and two virtual full-electric demonstrations reaching TRL6 in laboratory





NEMOSHIP

DIGITAL MODELS

Simcenter Amesim



Le Commandant Charcot



*Icebreaking
cruise ship*

Normand Drott



*Offshore
supply ship*

Full Electric Vessel



*Virtual
use case*

Fuel Cell Vessel



*Virtual
use case*


Digital Twin

A **1D simulation** for a specific use case, developed using a **virtual platform** and fed with *real data*


STANDARD DIGITAL TWIN FOR PONANT USE CASE



NEMOSHIP



SIEMENS
DIGITAL INDUSTRIES SOFTWARE
Simcenter
Amesim




Standard Digital Twin for Ponant use case contains:

- Ship resistance model + Weather resistance component
- 2 propellers
- 2 electric motors
- 4 transformers, one rectifier and one DC/DC converter
- Speed control components – converts the the speed profile into torque command for electric motors
- BESS - 4520 kWh Corvus Orca equivalent
- BMS with 4 battery modes: Peak Shaving, Charging, Discharging, ZEO.
- 6 gensets – 2 x Wartsila 31DF V10 5500 kW
– 4 x Wartsila 31DF V14 7720 kW
- Genset control system – ensures automatic starting and stopping of the gensets
- Load calculator – used to calculate power demand

HYBRID MODEL IMPLEMENTATION



NEMOSHIP




STANDARD DIGITAL TWIN FOR SOLSTAD USE CASE




NEMOSHIP

SLD Normand Drott
07.12.21 rev. As Is



SIEMENS
DIGITAL INDUSTRIES SOFTWARE
Simcenter
Amesim




Standard Digital Twin for Solstad use case contains:


- Ship resistance model + Weather resistance component
- 2 propellers
- 2 Main Engines with shaft generators + 2 PTIs
- 4 transformers, 2 rectifier and 2 DC/DC converter
- PTI speed and pitch calculator
- BESS - HP - 746 kWh Corvus Orca equivalent
- HE - 361 kWh Dolphin Energy NxtGen equivalent
- BMS with one battery mode: Peak Shaving
- 4 Auxiliary gensets – Caterpillar 3516c
- Genset control system – ensures automatic starting and stopping of the gensets
- Load calculator – used to calculate power demand



Full Electric Vessel



Fuel Cell Vessel





NEMOSHIP

NEMOSHIP DIGITAL CLOUD PLATFORM

nemoship.azurewebsites.net



Trains crew members to evaluate how different onboard configurations during past trips may have affected key performance indicators (KPIs), such as fuel consumption, power, and emissions. All results are archived for easy access and future reference.



Offers guidance to the crew on the operation of generators and the battery system for a future trip in order to minimize costs, emissions, or both of them.



Provides visualization and export capabilities for the simulation results.



Allows the user to analyze the impact of using the batteries for past trips or a custom time period from the past.





Facilitates access to a Battery Diagnostic Tool.

MODULAR CYBERSECURED ARCHITECTURE



NEMOSHIP







- Le Commandant Charcot
 - Statistical Analysis
 - Add Port to Port Trips
 - Past Simulation and Training
 - Single Leg Optimization
 - Voyage Optimization
 - Battery Diagnostic Tool

- Normand Drott
 - Past Simulation and Training
 - Trip Optimization
 - Battery Diagnostic Tool (Cidetec - under development)

- User Guides
 - User Manual - Le Commandant Charcot

- Virtual Use Cases
 - Full Electric
 - Fuel Cell

- roberta.luca.ext@siemens.com
 - Logout



Use Case

✓ *Le Commandant Charcot*

✓ Developed to assess **the impact of battery usage** over a defined period, focusing on various operational modes:


- *Zero Emissions*
- *Peak Shaving*
- *Spinning Reserve*

Objective

- ✓ Overview details for the full analyzed period
- ✓ Details per trip
- ✓ Details for a custom period

KPIs

- ✓ **Fuel Consumption**
- ✓ **GHG Emissions**
- ✓ **Methane CO₂eq Emissions**





Use Cases

- ✓ *Le Commandant Charcot*
- ✓ *Normand Drott*


- ✓ Allows the user to select a past trip and **modify various parameters** to analyze their impact on key performance indicators

Objective

- ✓ The core objective is to explore “what-if” scenarios for performance and efficiency evaluation

Amesim

- ✓ At the heart of this module is a **Simcenter Amesim digital model**, ensuring robust and realistic system behavior modeling
- ✓ The digital model was validated against real-world data provided by the vessel data system (Marorka and Dipai, for each vessel)





Use Cases

- ✓ *Le Commandant Charcot*
- ✓ *Normand Drott*


- ✓ Designed to support the crew in **optimizing the Battery Energy Storage System** for upcoming trips, aiming to reduce costs and emissions

Objective

- ✓ The **power profile** for the imported route is generated by the **digital model** developed in **Simcenter Amesim** based on the route, weather conditions, and different activities defined by the crew

Optimization

- ✓ The optimization algorithm uses the power profile and the user-defined parameters as inputs to **minimize costs** and **emissions**



INTERACTION WITH THE BATTERY DIAGNOSTIC TOOL




NEMOSHIP

Use Cases

- ✓ *Le Commandant Charcot*
- ✓ *Normand Drott*

- ✓ Defines predictive maintenance and diagnostic indicators based on the collected data and expected use of batteries

Objective






Use Cases

- ✓ *Le Commandant Charcot*
- ✓ *Normand Drott*

- ✓ Provide allocated storage space for documents that users wish to retain for future analysis or share with partners, with the option to restrict access as needed

Objective






Use Cases

- ✓ *Le Commandant Charcot*
- ✓ *Normand Drott*

Objective

- ✓ Provides comprehensive instructions for the use of the NEMOSHIP Digital Platform









Use Cases

- ✓ Full Electric
- ✓ Fuel Cell

Objective

- ✓ Allows the user to select a predefined trip and **modify various parameters** to analyze their impact on different key performance indicators






Purpose of the visit: gain practical insights into vessel operations, decision-making processes, and the energy management strategy

Key Activities

- Observed daily vessel operations
- Analyzed captain – chief engineer communication and decisions
- Reviewed Power Management System (PMS) setup and control
- Organized meetings with project partners and crew:
 - ❑ Captain
 - ❑ Chief engineer
 - ❑ Planning officer





NEMOSHIP



Co-funded by
the European Union

GA No. 101096324

Thank you for your attention!

Contact:

calin.husar@siemens.com

roberta.luca.ext@siemens.com



cidetec >
energy storage

Corvus  Energy

elkon

equinor 

In Extenso
Innovation Croissance

 **PONANT**

SDI

SIEMENS

 **SOLSTAD OFFSHORE**

VUB VRIJE
UNIVERSITEIT
BRUSSEL